# NSN 5315-00-431-0880

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-431-0880

## Head Style:

Pan no. 2 (r1 not required in item description)

## Chamfer Length:

Between 0.077 inches and 0.109 inches

## Diameter:

Between 0.994 inches and 0.996 inches

### **Under Head Length:**

Between 2.615 inches and 2.635 inches

## Hole Arrangement Style:

One end drilled

#### First Hole Diameter:

Between 0.161 inches and 0.181 inches

## Distance From Centerline Of Hole To End Of Pin:

0.196 inches

#### Hardness Rating:

26.5 rockwell c and 32.0 rockwell c

## Pin Chamfer Angle:

Between 14.5 degrees and 15.5 degrees

# Shear Strength:

117820 double pound

## **Pin Head Diameter:**

Between 1.171 inches and 1.203 inches

### **Special Features:**

Shank end may have either a chamfer or radius at the option of the vendor

### Height:

Between 0.109 inches and 0.141 inches

### Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

### Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification

3rd material response

### Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

### Style Designator:

Straight

## Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5315-00-431-0880

Headed Straight Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard): Mil-s-6758 spec.

