NSN 5315-00-433-4125

Headless Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-433-4125 First End Style: Chamfered **Hole Arrangement Style:** Both end drilled First Hole Diameter: Between 0.093 inches and 0.098 inches **Second Hole Diameter:** Between 0.093 inches and 0.098 inches **Distance From Centerline Of Hole To End Of Pin:** Between 0.220 inches and 0.280 inches **Center To Center Distance Between Holes:** Between 1.720 inches and 1.780 inches Pinlength: Between 2.220 inches and 2.280 inches Pindiameter: Between 0.4930 inches and 0.4980 inches First End Taper Length: Between 0.020 inches and 0.040 inches Second End Relationship With First End: Identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c First End Taper Angle: Between 44.0 degrees and 46.0 degrees **Surface Finish:** 63.0 microinches Material: Steel comp 3310 **Material Specification:** Mil-s-7393, comp 1 military specification single material response **Surface Treatment:** Chromium **Surface Treatment Specification:** Qq-c-320, type 1, class 2 federal specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A212a0

NSN 5315-00-433-4125

Headless Straight Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-7393 spec.