

View Online at <https://aerobasegroup.com/nsn/5315-00-435-0204>

**First End Style:**

Oval

**Second End Style:**

Slotted

**Shank Length:**

Between 0.310 inches and 1.690 inches

**Shoulder Diameter:**

Between 0.369 inches and 0.373 inches

**Shank Diameter:**

Between 0.248 inches and 0.250 inches

**Overall Length:**

2.120 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.125 inches and 0.130 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.125 inches

**Second End Slot Width:**

0.105 inches

**Second End Slot Depth:**

0.500 inches

**Second End Relationship With First End:**

Not identical

**Second Shank Diameter:**

Between 0.248 inches and 0.250 inches

**First End Location:**

Short shank end

**First End Outer Radius:**

0.160 inches

**Second Shank Length:**

Between 0.310 inches and 1.690 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.