

View Online at https://aerobasegroup.com/nsn/5315-00-435-5944

NSN 5315-00-435-5944 Headless Shoulder Pin - Page 1 of 2 First End Style: Chamfered Second End Style: Square Thread Class: 2a **Thread Direction: Right-hand Thread Length:** 0.440 inches Shank Length: 1.340 inches **Shoulder Width Across Flats:** 0.375 inches Shank Diameter: Between 0.307 inches and 0.308 inches **Overall Length:** 2.500 inches **End Application:** An/alq-119/184 commone First End Taper Length: 0.574 inches **Features Provided:** Casehardened Second End Relationship With First End: Not identical Hardness Rating: 37.0 rockwell c and 41.0 rockwell c Thread Size: 0.312 inches Second Shank Diameter: Between 0.311 inches and 0.312 inches **First End Location:** Large end First End Taper Angle: 15.0 degrees Second Shank Length: 1.060 inches Material: Steel comp 416 **Material Specification:**

Qq-s-764 federal specification single material response

NSN 5315-00-435-5944

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.