

View Online at <https://aerobasegroup.com/nsn/5315-00-439-2675>

**First End Style:**

Chamfered

**Second End Style:**

Round

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.288 inches

**Shank Length:**

0.350 inches

**Shoulder Diameter:**

Between 0.185 inches and 0.187 inches

**Shank Diameter:**

0.138 inches

**Overall Length:**

0.850 inches

**First End Taper Length:**

0.016 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.138 inches

**First End Location:**

Shank end

**First End Taper Angle:**

45.0 degrees

**Second End Outer Radius:**

Between 0.0925 inches and 0.0935 inches

**Special Features:**

0.089 in. Min 0.099 in. Maximum diameter 0.062 in. Lg thread relief on shank end and 0.025 in. Wide 0.035 in. Deep slot in shank end

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-764, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, e300 military specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-f-14072 spec.