

View Online at <https://aerobasegroup.com/nsn/5315-00-439-2676>

First End Style:

Chamfered

Second End Style:

Round

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.355 inches

Shank Length:

Between 0.415 inches and 0.485 inches

Shoulder Diameter:

Between 0.180 inches and 0.185 inches

Shank Diameter:

Between 0.089 inches and 0.091 inches

Overall Length:

1.000 inches

First End Taper Length:

0.031 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.112 inches

Second Shank Diameter:

0.112 inches

First End Location:

Short shank end

First End Taper Angle:

45.0 degrees

Second End Outer Radius:

Between 0.0445 inches and 0.0455 inches

Second Shank Length:

Between 0.415 inches and 0.485 inches

Special Features:

0.020 in. Wide 0.040 in. Deep slot in longest shank end and 0.060 in. Wide thread relief

Material:

Steel comp 303

Material Specification:

Qq-s-764, cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.