## NSN 5315-00-439-2676

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-439-2676

First End Style:
Chamfered
Second End Style:
Round
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.355 inches
Shank Length:
Between 0.415 inches and 0.485 inches
Shoulder Diameter:
Between 0.180 inches and 0.185 inches
Shank Diameter:
Between 0.089 inches and 0.091 inches
Overall Length:
1.000 inches
First End Taper Length:
0.031 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.112 inches
Second Shank Diameter:
0.112 inches
First End Location:
Short shank end
First End Taper Angle:
45.0 degrees
Second End Outer Radius:
Between 0.0445 inches and 0.0455 inches
Second Shank Length:
Between 0.415 inches and 0.485 inches
Special Features:
0.020 in. Wide 0.040 in. Deep slot in longest shank end and 0.060 in. Wide thread relief
Material:
Steel comp 303
Material Specification:
Qq-s-764, cond a federal specification single material response
Surface Treatment:
Passivate

## NSN 5315-00-439-2676

Headless Shoulder Pin - Page 2 of 2



Mil-f-14072, e300 military specification single treatment response

**Style Designator:** 

Shoulder

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.