

View Online at <https://aerobasegroup.com/nsn/5315-00-450-7343>

First End Style:

Chamfered

Second End Style:

Square

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.400 inches and 0.440 inches

Shank Length:

Between 1.160 inches and 1.200 inches

Shoulder Width Across Flats:

Between 0.615 inches and 0.630 inches

Shank Diameter:

Between 0.3725 inches and 0.3730 inches

Overall Length:

Between 1.760 inches and 1.800 inches

First End Taper Length:

Between 0.316 inches and 0.356 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.375 inches

Second Shank Diameter:

Between 0.373 inches and 0.375 inches

First End Location:

Long end

First End Taper Angle:

25.0 degrees

Surface Finish:

64.0 microinches outside diameter

Second Shank Length:

Between 0.450 inches and 0.550 inches

Special Features:

Longer shank relieved radially at shoulder end 0.314 in. Min 0.354 in. Maximum diameter 0.027 in. Min 0.067 in. Maximum radius of relief

Material:

Steel comp 316

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.