## NSN 5315-00-459-9551

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-459-9551

| First End Style:  |
|---|
| Chamfered   |
| Second End Style:   |
| Pointed   |
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.188 inches  |
| Shank Length:   |
| 0.180 inches  |
| Shoulder Width Across Flats:                                    |
| 0.250 inches  |
| Shank Diameter:   |
| 0.106 inches  |
| Overall Length:   |
| 0.590 inches  |
| Second End Taper Length:  |
| 0.166 inches  |
| Second End Relationship With First End:                         |
| Not identical   |
| Thread Size:  |
| 0.112 inches  |
| Second Shank Diameter:  |
| 0.112 inches  |
| First End Location:   |
| Short shank end   |
| Surface Finish:   |
| 125.000 microinches   |
| Second End Taper Angle:   |
| 15.0 degrees  |
| Second Shank Length:  |
| 0.377 inches  |
| Special Features:   |
| Chamfer on shorter shank end compatible with thread size        |
| Material:   |
| Steel comp 303  |
| Material Specification:   |
| Qq-s-764, cond a federal specification single material response |
| Surface Treatment:  |
|   |

Passivate

## NSN 5315-00-459-9551

Headless Shoulder Pin - Page 2 of 2



Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5002 spec.