## NSN 5315-00-460-0690

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-460-0690

First End Style: Chamkend Shank Length: 0.400 inches Shoulder Diameter: Between 0.419 inches and 0.420 inches Shank Diameter: Between 0.249 inches and 0.250 inches Overall Length: 1.600 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Stel comp 4340 Material Stel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment: Oxide Surface Treatment Specification: Mile-13924 military specification single treatment response Style Designato:: Shoulder Should	
Shank Length:0.810 inchesShoulder Diameter:Between 0.419 inches and 0.420 inchesShank Diameter:Between 0.249 inches and 0.250 inchesOverall Length:0.160 inchesFirst End Taper Length:0.030 inchesSecond End Relationship With First End:IdenticalHardness Rating:2.0 rockwell c and 38.0 rockwell cSecond Shank Diameter:Between 0.311 inches and 0.312 inchesFirst End Taper Angle:45.0 degreesSurface Finish:63.000 microinchesSecond Shank Length:1.280 inchesSite Location:81.000 microinchesSecond Shank Length:1.281 inchesMaterial:NaStel comp 4340Material:Material:NaSurface Treatment Specification:Mir-Lasger Angle:Strike Toratyper Angle:Strike Toratyper Angle:1.285 inchesMaterial:NaStrike Toratyper Angle:Strike Toratyper Angle:1.285 inchesMaterial:NaStrike Toratyper Angle:Strike Toratyper Angle:Material Specification:Material Specification single treatment responseStrike Toratyper Angle:NaStrike Toratyper Angle:Strike Toratyper Angle:Strike Toratyper Angle:Mit-1 Singer Angle:NaStrike Toratyper Angle:Strike Toratyper Angl	
0.810 inchesShoulder Diameter:Between 0.419 inches and 0.420 inchesShank Diameter:Between 0.249 inches and 0.250 inchesOverall Length:0.160 inchesFirst End Taper Length:0.030 inchesSecond End Relationship With First End:IdenticalHardness Rating:2.0 rackwell c and 38.0 rockwell cSecond Shank Diameter:Between 0.311 inches and 0.312 inchesFirst End Location:Both endsFirst End Taper Angle:45.0 degreesSurface Finish:6.3000 microinchesSecond Shank Length:1.285 inchesMaterial:Naterial:Stel comp 4340Material:OxideSurface Treatment:OxideSurface Treatment specification:Mit-13924 military specification single treatment responseStyle Designator:Naterial:Naterial:Naterial:Naterial:Naterial:Mit-13924 military specification single treatment responseStyle Designator:Naterial:Naterial:Naterial:Naterial:Naterial:Style Designator:Naterial:Naterial:Style Designator:Naterial:Naterial:Naterial:Style Designator:Style Designator:Naterial:Style Designator:Naterial:Style Designator:Naterial:<	
Shoulder Diameter:Between 0.419 inches and 0.420 inchesShank Diameter:Between 0.249 inches and 0.250 inchesOverall Length:5.160 inchesFirst End Taper Length:0.030 inchesSecond End Relationship With First End:IdenticalHardness Rating:32.0 rockwell c and 38.0 rockwell cSecond Shank Diameter:Between 0.311 inches and 0.312 inchesFirst End Taper Angle:45.0 degreesSurface Finish:63.000 microinchesSecond Shank Length:1.285 inchesMaterialMaterialMaterialSteel comp 4340Material Specification:Arise Afta san standard single material responseSurface Treatment SpecificationMite-13924 military specification single treatment responseStyle Designator:ShoulderShoulde	
Between 0.419 inches and 0.420 inches         Shank Diameter:         Between 0.249 inches and 0.250 inches         Overall Length:         5.160 inches         First End Taper Length:         0.030 inches         Second End Relationship With First End:         Identical         Hardness Rating:         3.2.0 rockwell c and 38.0 rockwell c         Second Shank Diameter:         Between 0.311 inches and 0.312 inches         First End Location:         Both ends         First End Taper Angle:         45.0 degrees         Surface Finish:         63.000 microinches         Between 0.311 inches and 0.312 inches         First End Location:         80th ends         First End Taper Angle:         45.0 degrees         Surface Finish:         63.000 microinches         Second Shank Length:         1.285 inches         Material:         Steel comp 4340         Material Specification:         Mit-o-13924 military specification single treatment response         Style Designator:         Shoulder         Shoulder         Shoulder         Shoulder	
Shank Diameter: Between 0.249 inches and 0.250 inches Overall Length: 5.160 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment: Oxide Surface Treatment Specification single treatment response Style Designator: Shoulder Sho	
Between 0.249 inches and 0.250 inches Overall Length: 5.160 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 asen standard single material response Surface Treatment Specification single treatment response Style Designator: Shoulder Shoulder Shoulder First End End Taper Length: Na Curi Of Measure: First End Taper Length: First End Taper Taper Length: First End Taper Taper Length: First End Taper Angle: Style Designator: Shoulder First End Taper Length: First End Taper Angle: Style Designator: Shoulder Shoulde	
Overall Length:         5.160 inches         First End Taper Length:         0.030 inches         Second End Relationship With First End:         Identical         Hardness Rating:         32.0 rockwell c and 38.0 rockwell c         Second Shank Diameter:         Between 0.311 inches and 0.312 inches         First End Location:         Both ends         First End Taper Angle:         45.0 degrees         Surface Finish:         63.000 microinches         Second Shank Length:         1.285 inches         Material         Steel comp 4340         Material Specification:         Ams 6415 assn standard single material response         Surface Treatment:         Cixide         Surface Treatment Specification single treatment response	Shank Diameter:
5.180 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material Steel comp 4340 Material Specification: Material Specification single material response Surface Treatment: Cixide Surface Treatment: Mit-o-13924 military specification single treatment response Syle Designator: Na	Between 0.249 inches and 0.250 inches
First End Taper Length:         0.030 inches         Second End Relationship With First End:         Identical         Hardness Rating:         32.0 rockwell c and 38.0 rockwell c         Second Shank Diameter:         Between 0.311 inches and 0.312 inches         First End Location:         Both ends         First End Taper Angle:         45.0 degrees         Surface Finish:         63.000 microinches         Second Shank Length:         1.285 inches         Material:         Steel comp 4340         Material Specification:         Ans 6415 assn standard single material response         Surface Treatment:         Oxide         Surface Treatment:         Oxide         Surface Treatment Specification:         Mil-c-13924 military specification single treatment response         Style Designator:         Shoulder         Sheif Life:         N/a         Unit Of Measure:         -         Demilitarization:	Overall Length:
0.030 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment: Mih-c-13924 military specification single treatment response Surface Treatment: Naile-C-13924 military specification single treatment response Surface Treatment: Naile-C-13924 military specification single treatment response Surface Treatment: Naile-C-13924 military specification single treatment response Mih-c-13924 military specification single treatment response Surface Treatment: Naile-C-13924 military specification single treatment response Surface Treatment: Surfa	5.160 inches
Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification single treatment response Style Designator: Shoulder Should	First End Taper Length:
Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Stel comp 4340 Material Specification: Ans 6415 assn standard single material response Surface Treatment Civide Surface Treatment Specification single treatment response Style Designato: Shoulder Should	0.030 inches
Hardness Rating:         32.0 rockwell c and 38.0 rockwell c         Second Shank Diameter:         Between 0.311 inches and 0.312 inches         First End Location:         Both ends         First End Taper Angle:         45.0 degrees         Surface Finish:         63.000 microinches         Second Shank Length:         1.285 inches         Material:         Steel comp 4340         Material Specification:         Ams 6415 assn standard single material response         Surface Treatment Specifications         Milc-13924 military specification single treatment response         Syle Designator:         Shoulder         Shoulder<	Second End Relationship With First End:
32.0 rockwell c         Second Shank Diameter:         Between 0.311 inches and 0.312 inches         First End Location:         Both ends         First End Taper Angle:         45.0 degrees         Surface Finish:         63.000 microinches         Second Shank Length:         1.285 inches         Material:         Steel comp 4340         Material Specification:         Ams 6415 assn standard single material response         Surface Treatment:         Oxide         Surface Treatment Specification single treatment response         Shoulder         Direct Measure:         N/a         End         Direct Measure:         Tot Measure:         Free         Shoulder         Shoulder         Shoulder	Identical
Second Shank Diameter: Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Arns 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification single treatment response Surface Treatment Specification single treatment response Surface Treatment: Nil-c-13924 military specification single treatment response Syle Designator: Shoulder Shoulder Shoulder Shoulder Material: N/a Unit of Measure:  Demilitarization:	Hardness Rating:
Between 0.311 inches and 0.312 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification single treatment response Style Designator: Shoulder Shelf Life: N/a Unit of Measure:	32.0 rockwell c and 38.0 rockwell c
First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: 1.285 inches Material: Steel comp 4340 Material Specification: Atms 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment: Oxide Surface Treatment Specification single treatment response Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: 	Second Shank Diameter:
Both ends         First End Taper Angle:         45.0 degrees         Surface Finish:         63.000 microinches         Second Shank Length:         1.285 inches         Material:         Steel comp 4340         Material Specification:         Ams 6415 assn standard single material response         Surface Treatment:         Oxide         Surface Treatment Specification single treatment response         Shulder         Shoulder         Shoulder         Init of Measure:            T         Dring Measure:            Dimilitarization:	Between 0.311 inches and 0.312 inches
First End Taper Angle: 45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Arns 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification single treatment response Style Designator: Shoulder Shoulde	First End Location:
45.0 degrees Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 military specification single treatment response Sufface Treatment Specification single treatment response Sufface Treatment Specification single treatment response Surface Treatment Specification single treatment response Sufface Treatment Specification single tre	Both ends
Surface Finish: 63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shoulder Shoulder Ma Dit of Measure: 	First End Taper Angle:
63.000 microinches Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: 	45.0 degrees
Second Shank Length: 1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification single treatment response Surface Treatment Specification single treatment response Style Designator: Shoulder Shoulder Ma Unit Of Measure: 	Surface Finish:
1.285 inches Material: Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: 	63.000 microinches
Material:   Steel comp 4340   Material Specification:   Ams 6415 assn standard single material response   Surface Treatment:   Oxide   Surface Treatment Specification:   Mil-c-13924 military specification single treatment response   Style Designator:   Shoulder   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:	Second Shank Length:
Steel comp 4340 Material Specification: Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shoulder Sheif Life: N/a Unit Of Measure:  Demilitarization:	1.285 inches
Material Specification:Ams 6415 assn standard single material responseSurface Treatment:OxideSurface Treatment Specification:Mil-c-13924 military specification single treatment responseStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:-Demilitarization:	Material:
Ams 6415 assn standard single material response Surface Treatment: Oxide Surface Treatment Specification: Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: 	Steel comp 4340
Surface Treatment: Oxide Surface Treatment Specification: MiI-c-13924 military specification single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: 	Material Specification:
Oxide Surface Treatment Specification: Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization:	Ams 6415 assn standard single material response
Surface Treatment Specification: Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure:  Demilitarization:	Surface Treatment:
Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization:	Oxide
Mil-c-13924 military specification single treatment response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment Specification:
Style Designator: Shoulder Shelf Life: N/a Unit Of Measure:  Demilitarization:	
Shoulder Shelf Life: N/a Unit Of Measure:  Demilitarization:	Style Designator:
Shelf Life: N/a Unit Of Measure:  Demilitarization:	
N/a Unit Of Measure:  Demilitarization:	
Unit Of Measure:  Demilitarization:	
 Demilitarization:	

## NSN 5315-00-460-0690

Headless Shoulder Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard):

Mil-c-13924 spec.

