NSN 5315-00-460-2967

Headless Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-460-2967 First End Style: Chamfered **Hole Arrangement Style:** Both end drilled First Hole Diameter: Between 0.074 inches and 0.080 inches **Second Hole Diameter:** Between 0.074 inches and 0.080 inches **Distance From Centerline Of Hole To End Of Pin:** 0.093 inches **Center To Center Distance Between Holes:** 2.436 inches Pinlength: 2.625 inches Pindiameter: Between 0.2480 inches and 0.2490 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Surface Finish: 125.0 microinches outside diameter Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, 5.4.1 military standard single treatment response **Test Data Document:** 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A212a0

No

NSN 5315-00-460-2967

Headless Straight Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.