

View Online at <https://aerobasegroup.com/nsn/5315-00-470-7933>

First End Style:

Chamfered

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.104 inches and 0.111 inches

Second Hole Diameter:

Between 0.104 inches and 0.111 inches

Distance From Centerline Of Hole To End Of Pin:

0.125 inches

Center To Center Distance Between Holes:

3.000 inches

Pinlength:

3.250 inches

Pindiameter:

Between 0.4350 inches and 0.4360 inches

First End Taper Length:

0.030 inches

Second End Relationship With First End:

Identical

First End Taper Angle:

45.0 degrees

Surface Finish:

63.0 microinches outside diameter

Special Features:

Solid film lubricant mil-I-8937

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Qq-c-320, cl 2 federal specification single treatment response

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-18732 spec.