NSN 5315-00-476-5126

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-476-5126

| First End Style: |
|---|
| Chamfered |
| Head Style: |
| Tee no. 3 |
| Head Length: |
| Between 0.985 inches and 1.015 inches |
| Under Head Length: |
| Between 1.297 inches and 1.327 inches |
| First Step Diameter: |
| Between 0.428 inches and 0.432 inches |
| First Step Length: |
| Between 0.985 inches and 1.015 inches |
| Second Step Diameter: |
| Between 0.235 inches and 0.265 inches |
| Second Step Length: |
| Between 0.297 inches and 0.327 inches |
| First End Taper Length: |
| 0.031 inches |
| Width Across Flats: |
| Between 0.516 inches and 0.546 inches |
| Features Provided: |
| Casehardened |
| Hardness Rating: |
| 88.0 rockwell superficial 15-n and 91.0 rockwell superficial 15-n |
| First End Taper Angle: |
| 45.0 degrees |
| Surface Finish: |
| 63.0 microinches head top |
| Height: |
| Between 0.110 inches and 0.140 inches |
| Material: |
| Steel |
| Material Specification: |
| Qq-s-631 1015 to 1025 federal specification single material response or qq-s-634 1015 to 1025 federal specification single material |
| response or qq-s-637, b1112, b1113, 1213 or 1215 federal specification single material response |
| Surface Treatment: |
| Phosphate manganese |
| Surface Treatment Specification: |
| Mil-p-16232, cl 1 military specification single treatment response |
| Style Designator: |
| Shoulder |
| Shelf Life: |
| N/a |

NSN 5315-00-476-5126

Headed Shoulder Pin - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.