NSN 5315-00-476-5126

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-476-5126

First End Style:
Chamfered
Head Style:
Tee no. 3
Head Length:
Between 0.985 inches and 1.015 inches
Under Head Length:
Between 1.297 inches and 1.327 inches
First Step Diameter:
Between 0.428 inches and 0.432 inches
First Step Length:
Between 0.985 inches and 1.015 inches
Second Step Diameter:
Between 0.235 inches and 0.265 inches
Second Step Length:
Between 0.297 inches and 0.327 inches
First End Taper Length:
0.031 inches
Width Across Flats:
Between 0.516 inches and 0.546 inches
Features Provided:
Casehardened
Hardness Rating:
88.0 rockwell superficial 15-n and 91.0 rockwell superficial 15-n
First End Taper Angle:
45.0 degrees
Surface Finish:
63.0 microinches head top
Height:
Between 0.110 inches and 0.140 inches
Material:
Steel
Material Specification:
Qq-s-631 1015 to 1025 federal specification single material response or qq-s-634 1015 to 1025 federal specification single material
response or qq-s-637, b1112, b1113, 1213 or 1215 federal specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232, cl 1 military specification single treatment response
Style Designator:
Shoulder
Shelf Life:
N/a

NSN 5315-00-476-5126

Headed Shoulder Pin - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.