NSN 5315-00-479-0249

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-479-0249 First End Style: Chamfered **Shank Length:** Between 0.378 inches and 0.398 inches Shoulder Diameter: Between 0.4365 inches and 0.4370 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Overall Length:** Between 4.330 inches and 4.370 inches **Undercut Diameter:** Between 0.312 inches and 0.322 inches **Undercut Width:** Between 0.042 inches and 0.062 inches **Second Undercut Width:** Between 0.042 inches and 0.062 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.125 inches and 0.130 inches **Distance From Centerline Of Hole To End Of Pin:** Between 0.953 inches and 0.983 inches First End Taper Length: 0.025 inches

Second End Relationship With First End:

Identical

Second Shank Diameter:

Between 0.3740 inches and 0.3745 inches

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Surface Finish:

63.000 microinches

Second Shank Length:

Between 0.406 inches and 0.426 inches

Material:

Titanium

Material Specification:

Mms124 7al-4moti76301 mfr ref single material response

Style Designator:

Undercut

NSN 5315-00-479-0249

Headless Shoulder Pin - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0