## NSN 5315-00-480-3578



Headless Straight Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-480-3578 First End Style: Chamfered **Hole Arrangement Style:** Both end drilled First Hole Diameter: 0.160 inches **Second Hole Diameter:** 0.160 inches **Distance From Centerline Of Hole To End Of Pin:** 0.250 inches **Center To Center Distance Between Holes:** 11.000 inches Pinlength: 11.500 inches Pindiameter: Between 0.8740 inches and 0.8745 inches First End Taper Length: 0.130 inches **Features Provided:** Casehardened **Second End Relationship With First End:** Identical **Hardness Rating:** 57.0 rockwell c and 62.0 rockwell c First End Taper Angle: 45.0 degrees **Surface Finish:** 32.0 microinches outside diameter Material: Steel comp 4118 or steel comp 4140 or steel comp 4320 or steel comp 4340 or steel comp 8620 or steel comp 8640 or steel comp 8740 **Material Specification:** Qq-s-624 federal specification all material responses **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232 ty m cl 4b military specification single treatment response

**Unit Of Measure:** 

Shelf Life:

**Demilitarization:** 

No

N/a

## NSN 5315-00-480-3578

Headless Straight Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.