## NSN 5315-00-487-3892

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-487-3892

|    | First End Style:                                       |
|----|--|
| -  | Chamfered  |
|    | Iole Arrangement Style:                                |
| E  | Both end drilled                                       |
| F  | First Hole Diameter:                                   |
| E  | Between 0.106 inches and 0.113 inches                  |
| S  | Second Hole Diameter:                                  |
| E  | Between 0.106 inches and 0.113 inches                  |
| D  | Distance From Centerline Of Hole To End Of Pin:        |
| 0  | 0.160 inches   |
| C  | Center To Center Distance Between Holes:               |
| 5  | 5.900 inches   |
| P  | Pinlength:   |
| 6  | 5.270 inches   |
| P  | Pindiameter:   |
| 0  | 0.5000 inches  |
| F  | First End Taper Length:                                |
| 0  | 0.030 inches   |
| S  | Second End Relationship With First End:                |
| lo | dentical   |
| F  | First End Taper Angle:                                 |
| B  | Between 42.0 degrees and 48.0 degrees                  |
| S  | Surface Finish:  |
| 1  | 25.0 microinches                                       |
| N  | Naterial:  |
| S  | Steel comp 303se                                       |
| N  | Naterial Specification:                                |
| C  | Qq-p-35 federal specification single material response |
| S  | Surface Treatment:                                     |
| F  | Passivate  |
| S  | Surface Treatment Specification:                       |
| 1  | 71, 5.4.1 military standard single treatment response  |
| S  | Shelf Life:  |
| Ν  | l/a  |
| ι  | Jnit Of Measure:                                       |
|    | -  |
| C  | Demilitarization:                                      |
| Ν  | 10   |
| F  | iig:   |
| A  | A212a0   |