

View Online at <https://aerobasegroup.com/nsn/5315-00-487-4070>

First End Style:

Chamfered

Shank Length:

2.450 inches

Shoulder Diameter:

Between 0.740 inches and 0.750 inches

Shank Diameter:

Between 0.623 inches and 0.624 inches

Overall Length:

22.320 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.219 inches and 0.224 inches

Second Hole Diameter:

Between 0.219 inches and 0.224 inches

Distance From Centerline Of Hole To End Of Pin:

0.600 inches

Center To Center Distance Between Holes:

21.140 inches

First End Taper Length:

0.040 inches

Second End Relationship With First End:

Identical

Second Shank Diameter:

Between 0.623 inches and 0.624 inches

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Special Features:

Angle between centerlines of holes 90.0 degrees

Material:

Steel comp 4130

Material Specification:

Mil-s-6758, cond d4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.