# NSN 5315-00-487-4912

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-487-4912

## Head Diameter:

Between 0.360 inches and 0.450 inches

## Shank Diameter:

Between 0.1870 inches and 0.1885 inches

## **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

# **Detent Quantity:**

## 2

**Actuation Method:** 

Push button

Grip Length:

Between 0.700 inches and 0.720 inches

**Actuation Type:** 

Pull and push

Hardness Rating:

40.0 rockwell c spindle

## Shoulder To Head End Distance:

0.935 inches

## **Pin Attachment Type:**

Hook

# Detent To Tapered End Distance:

Between 0.360 inches and 0.410 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

Ring handle

Shelf Life:

N/a

#### Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A212a0