

View Online at <https://aerobasegroup.com/nsn/5315-00-490-4632>

**Handle Length:**

Between 2.500 inches and 3.100 inches

**Shank Diameter:**

Between 0.7470 inches and 0.7485 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.900 inches and 2.920 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

73600 double pounds per square inch

**Shoulder To Head End Distance:**

1.720 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.640 inches and 0.670 inches

**Special Features:**

Steel attaching hook or ring, qq-w-423, comp 302 or qq-w-428, type 1, 2, or 3, cond a or b with cadmium, qq-p-416, type 2, cl 3 or passivated surface qq-p-35

**Material:**

Steel spring

**Material Specification:**

Qq-w-470 federal specification single material response spring

**Surface Treatment:**

Passivate detent

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response shank

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.