# NSN 5315-00-490-4632

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-490-4632

### Handle Length:

Between 2.500 inches and 3.100 inches

#### Shank Diameter:

Between 0.7470 inches and 0.7485 inches

# **Detent Quantity:**

2

### **Actuation Method:**

Push button

#### Grip Length:

Between 2.900 inches and 2.920 inches

#### Actuation Type:

Push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

#### Shear Strength:

73600 double pounds per square inch

# Shoulder To Head End Distance:

1.720 inches

#### Pin Attachment Type:

Hook or ring

# **Detent To Tapered End Distance:**

Between 0.640 inches and 0.670 inches

## **Special Features:**

Steel attaching hook or ring, qq-w-423, comp 302 or qq-w-428, type 1, 2, or 3, cond a or b with cadmium, qq-p-416, type 2, cl 3 or

passivated surface qq-p-35

#### Material:

Steel spring

# Material Specification:

Qq-w-470 federal specification single material response spring

#### Surface Treatment:

Passivate detent

#### **Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response shank

#### Style Designator:

T handle

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A212a0

# NSN 5315-00-490-4632

Quick Release Pin - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6758 spec.

