NSN 5315-00-490-4632

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-490-4632 Handle Length: Between 2.500 inches and 3.100 inches **Shank Diameter:** Between 0.7470 inches and 0.7485 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 2.900 inches and 2.920 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 73600 double pounds per square inch **Shoulder To Head End Distance:** 1.720 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.640 inches and 0.670 inches **Special Features:** Steel attaching hook or ring, qq-w-423, comp 302 or qq-w-428, type 1, 2, or 3, cond a or b with cadmium, qq-p-416, type 2, cl 3 or passivated surface qq-p-35 Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response shank **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A212a0

NSN 5315-00-490-4632

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.