

View Online at <https://aerobasegroup.com/nsn/5315-00-492-3653>

First End Style:

Chamfered

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.172 inches and 0.234 inches

Second Hole Diameter:

Between 0.172 inches and 0.234 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.281 inches and 0.344 inches

Center To Center Distance Between Holes:

Between 4.250 inches and 4.312 inches

Pinlength:

Between 4.875 inches and 4.938 inches

Pindiameter:

1.0000 inches

First End Taper Length:

Between 0.031 inches and 0.094 inches

Second End Relationship With First End:

Identical

First End Taper Angle:

Between 44.5 degrees and 45.5 degrees

Material:

Steel comp 1018 or steel comp 1020 or steel comp 1025

Material Specification:

Mil-s-7097 cond b4 military specification all material responses

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416 type 1 cl 1 federal specification 1st treatment response or qq-z-325 type 1 cl 3 federal specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-7097 spec.