

View Online at <https://aerobasegroup.com/nsn/5315-00-494-3197>

Head Diameter:

Between 0.510 inches and 0.630 inches

Shank Diameter:

Between 0.4345 inches and 0.4360 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.500 inches and 1.520 inches

Actuation Type:

Pull and push

Features Provided:

Drive out feature and lock open feature

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shoulder To Head End Distance:

1.000 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.510 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium shank and chromate shank

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response shank

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.