

View Online at <https://aerobasegroup.com/nsn/5315-00-494-8525>

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Button Handle Diameter:**

Between 0.720 inches and 0.800 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: wasp class lhd; support equipment, c-130 aircraft; helicopter, seasprite h-2; aircraft, hercules c-130; helicopter, rh-53; helicopter, apache ah-64; iwo jima class lph; aircraft, starlifter c-141; aircraft, stratolifter c-135; airborne mine counter measure

**Grip Length:**

Between 1.900 inches and 1.920 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.890 inches

**Pin Attachment Type:**

Hook and retaining chain

**Detent To Tapered End Distance:**

Between 0.260 inches and 0.290 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0