

View Online at <https://aerobasegroup.com/nsn/5315-00-494-8525>

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Button Handle Diameter:

Between 0.720 inches and 0.800 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

W/s: wasp class lhd; support equipment, c-130 aircraft; helicopter, seasprite h-2; aircraft, hercules c-130; helicopter, rh-53; helicopter, apache ah-64; iwo jima class lph; aircraft, starlifter c-141; aircraft, stratolifter c-135; airborne mine counter measure

Grip Length:

Between 1.900 inches and 1.920 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.890 inches

Pin Attachment Type:

Hook and retaining chain

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0