NSN 5315-00-495-6522

Headed Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-495-6522

First End Style:
Counterbored w/o through hole
Head Style:
Dee
Distance From Centerline To Flat:
0.880 inches
Diameter:
1.375 inches
Effective Length:
4.120 inches
Undercut Diameter:
1.250 inches
Under Head Length:
4.920 inches
Undercut Width:
0.120 inches
Second Undercut Width:
0.120 inches
Second Undercut Diameter:
1.440 inches
Hole Arrangement Style:
Both end drilled
First Hole Diameter:
0.124 inches
Second Hole Diameter:
0.124 inches
Distance From Centerline Of Hole To End Of Pin:
2.120 inches
Center To Center Distance Between Holes:
0.380 inches
First End Counterbore Diameter:
0.880 inches
First End Counterbore Depth:
0.120 inches
Features Provided:
Casehardened
Hardness Rating:
25.0 rockwell c and 35.0 rockwell c
Pin Head Diameter:
2.550 inches
Surface Finish:
63.0 microinches long shank

NSN 5315-00-495-6522 Headed Grooved Pin - Page 2 of 2



Special Features:
Axial hole 1/8-27npt x 3.000 deepfrom head; point is 1.375-18unef-3a
Height:
0.380 inches
Material:
Steel comp 8620
Material Specification:
Mil-s-13048 military specification single material response
Surface Treatment:
Lubricant
Surface Treatment Specification:
Mil-I-8937 military specification single treatment response
Style Designator:
Groove
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):
Mil-s-13048 spec.