NSN 5315-00-495-6522

Headed Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-495-6522

First End Style:

Counterbored w/o through hole

Head Style:

Dee

Distance From Centerline To Flat:

0.880 inches

Diameter:

1.375 inches

Effective Length:

4.120 inches

Undercut Diameter:

1.250 inches

Under Head Length:

4.920 inches

Undercut Width:

0.120 inches

Second Undercut Width:

0.120 inches

Second Undercut Diameter:

1.440 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

0.124 inches

Second Hole Diameter:

0.124 inches

Distance From Centerline Of Hole To End Of Pin:

2.120 inches

Center To Center Distance Between Holes:

0.380 inches

First End Counterbore Diameter:

0.880 inches

First End Counterbore Depth:

0.120 inches

Features Provided:

Casehardened

Hardness Rating:

25.0 rockwell c and 35.0 rockwell c

Pin Head Diameter:

2.550 inches

Surface Finish:

63.0 microinches long shank

NSN 5315-00-495-6522

Headed Grooved Pin - Page 2 of 2



Special Features:

Axial hole 1/8-27npt x 3.000 deepfrom head; point is 1.375-18unef-3a

Height:

0.380 inches

Material:

Steel comp 8620

Material Specification:

Mil-s-13048 military specification single material response

Surface Treatment:

Lubricant

Surface Treatment Specification:

Mil-I-8937 military specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-13048 spec.