

View Online at <https://aerobasegroup.com/nsn/5315-00-500-2202>

First End Style:

Chamfered

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.203 inches and 0.219 inches

Second Hole Diameter:

Between 0.203 inches and 0.219 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.281 inches and 0.344 inches

Center To Center Distance Between Holes:

Between 3.219 inches and 3.281 inches

Pinlength:

Between 3.844 inches and 3.906 inches

Pindiameter:

Between 1.1780 inches and 1.1800 inches

First End Taper Length:

Between 0.031 inches and 0.094 inches

Second End Relationship With First End:

Identical

Hardness Rating:

25.0 rockwell c and 30.0 rockwell c

First End Taper Angle:

Between 43.0 degrees and 47.0 degrees

Material:

Steel

Surface Treatment:

Phosphate manganese or phosphate zinc

Surface Treatment Specification:

Mil-p-16232, ty m cl 1 military specification 1st treatment response or mil-p-16232, ty z cl 1 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.