

View Online at <https://aerobasegroup.com/nsn/5315-00-503-7304>

**First End Style:**

Oval

**Second End Style:**

Square

**Shank Length:**

Between 0.650 inches and 0.660 inches

**Shoulder Diameter:**

Between 0.365 inches and 0.375 inches

**Shank Diameter:**

Between 0.218 inches and 0.220 inches

**Overall Length:**

Between 0.940 inches and 0.950 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

59.0 rockwell c and 61.0 rockwell c

**Second Shank Diameter:**

Between 0.247 inches and 0.249 inches

**First End Location:**

Short shank end

**First End Outer Radius:**

0.124 inches

**Surface Finish:**

63.0 microinches both ends

**Second Shank Length:**

Between 0.190 inches and 0.200 inches

**Material:**

Steel comp 1046 or steel comp 1048 or steel comp 1050 or steel comp 1049

**Material Specification:**

Qq-s-634 federal specification all material responses

**Surface Treatment:**

Phosphate manganese or phosphate zinc

**Surface Treatment Specification:**

Mil-p-16232, ty m, cl 3 military specification 1st treatment response or mil-p-16232, ty z, cl 1 military specification 2nd treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-p-16232 spec.