## NSN 5315-00-513-5206

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-513-5206 **Head Diameter:** 0.708 inches **Shank Diameter:** Between 0.3905 inches and 0.3920 inches **Ring Handle Diameter:** Between 1.080 inches and 1.394 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 0.788 inches and 0.808 inches **Actuation Type:** Pull and push **Hardness Rating:** 58.0 rockwell c detent and 62.0 rockwell c detent **Shear Strength:** 19996 double pounds per square inch **Shoulder To Head End Distance:** 1.062 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** Between 0.315 inches and 0.393 inches Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response shank **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-00-513-5206

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.