# NSN 5315-00-514-6948

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-514-6948

## Shank Diameter:

Between 0.4970 inches and 0.4985 inches

## **Button Handle Diameter:**

Between 1.300 inches and 1.400 inches

# **Detent Quantity:**

2

#### **Actuation Method:**

Push button

#### Grip Length:

Between 4.300 inches and 4.320 inches

#### **Actuation Type:**

Push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shear Strength:

36800 double pound

## Shoulder To Head End Distance:

1.190 inches

## Pin Attachment Type:

Hook or ring

# Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

Button

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A212a0