

View Online at <https://aerobasegroup.com/nsn/5315-00-515-6910>

**First End Style:**

Chamfered and counterbored

**Head Style:**

Flat chamfer

**Under Head Length:**

1.590 inches

**First Step Diameter:**

0.623 inches

**First Step Length:**

0.190 inches

**Second Step Diameter:**

0.344 inches

**Second Step Length:**

1.230 inches

**Third Step Diameter:**

0.3125 inches

**Third Step Length:**

0.120 inches

**First End Counterbore Diameter:**

0.060 inches

**First End Counterbore Depth:**

0.090 inches

**First End Taper Length:**

0.030 inches

**Hardness Rating:**

38.0 rockwell c and 42.0 rockwell c

**First End Taper Angle:**

45.0 degrees

**Pin Head Diameter:**

0.423 inches

**Height:**

0.250 inches

**Material:**

Steel

**Material Specification:**

Astm-a-322 assn standard single material response or astm-a331 assn standard single material response or astm-a108 assn standard single material response or astm-a576 assn standard single material response

**Surface Treatment:**

Phosphate manganese or phosphate zinc

**Surface Treatment Specification:**

Dod-p-16232 military specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

spec.