## NSN 5315-00-516-0355

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-516-0355 First End Style: Chamfered **Second End Style:** Square **Shank Length:** Between 0.6277 inches and 0.6307 inches Shoulder Diameter: 0.438 inches **Shank Diameter:** Between 0.245 inches and 0.255 inches **Overall Length:** 2.031 inches **Undercut Diameter:** Between 0.185 inches and 0.195 inches **Undercut Width:** Between 0.070 inches and 0.075 inches **Second Undercut Width:** Any acceptable **Second Undercut Diameter:** Any acceptable First End Taper Length: 0.016 inches **Second End Relationship With First End:** Not identical Hardness Rating: 70.0 rockwell b **Second Shank Diameter:** Between 0.307 inches and 0.309 inches **First End Location:** Long end First End Taper Angle: 45.0 degrees **Second Shank Length:** Between 0.6277 inches and 0.6307 inches **Special Features:** Flat of larger diameter end of shank is drilled 0.219 in. Diameter 0.250 in. Deep Material: Steel **Surface Treatment:** Cadmium or zinc **Style Designator:** 

Undercut

## NSN 5315-00-516-0355

Headless Shoulder Pin - Page 2 of 2



	Life	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0