## NSN 5315-00-519-9526

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-519-9526

Chamfered Shank Length: Between 0.085 inches and 0.135 inches Shoulder Diameter: Between 0.215 inches and 0.225 inches Shank Diameter: Between 0.1512 inches and 0.1522 inches Overall Length: Between 0.315 inches and 0.335 inches Undercut Diameter: Between 0.141 inches and 0.146 inches Undercut Width: Between 0.025 inches and 0.055 inches Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 36.0 rockwell c
Between 0.085 inches and 0.135 inches  Shoulder Diameter:  Between 0.215 inches and 0.225 inches  Shank Diameter:  Between 0.1512 inches and 0.1522 inches  Overall Length:  Between 0.315 inches and 0.335 inches  Undercut Diameter:  Between 0.141 inches and 0.146 inches  Undercut Width:  Between 0.025 inches and 0.055 inches  Second Undercut Width:  Between 0.090 inches and 0.130 inches  Second Undercut Diameter:  Between 0.162 inches and 0.167 inches  First End Taper Length:  0.020 inches  Second End Relationship With First End:  Identical  Hardness Rating:
Shoulder Diameter: Between 0.215 inches and 0.225 inches Shank Diameter: Between 0.1512 inches and 0.1522 inches Overall Length: Between 0.315 inches and 0.335 inches Undercut Diameter: Between 0.141 inches and 0.146 inches Undercut Width: Between 0.025 inches and 0.055 inches Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
Between 0.215 inches and 0.225 inches  Shank Diameter:  Between 0.1512 inches and 0.1522 inches  Overall Length:  Between 0.315 inches and 0.335 inches  Undercut Diameter:  Between 0.141 inches and 0.146 inches  Undercut Width:  Between 0.025 inches and 0.055 inches  Second Undercut Width:  Between 0.090 inches and 0.130 inches  Second Undercut Diameter:  Between 0.162 inches and 0.167 inches  First End Taper Length:  0.020 inches  Second End Relationship With First End:  Identical  Hardness Rating:
Shank Diameter: Between 0.1512 inches and 0.1522 inches Overall Length: Between 0.315 inches and 0.335 inches Undercut Diameter: Between 0.141 inches and 0.146 inches Undercut Width: Between 0.025 inches and 0.055 inches Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
Between 0.1512 inches and 0.1522 inches  Overall Length:  Between 0.315 inches and 0.335 inches  Undercut Diameter:  Between 0.141 inches and 0.146 inches  Undercut Width:  Between 0.025 inches and 0.055 inches  Second Undercut Width:  Between 0.090 inches and 0.130 inches  Second Undercut Diameter:  Between 0.162 inches and 0.167 inches  First End Taper Length:  0.020 inches  Second End Relationship With First End:  Identical  Hardness Rating:
Overall Length: Between 0.315 inches and 0.335 inches Undercut Diameter: Between 0.141 inches and 0.146 inches Undercut Width: Between 0.025 inches and 0.055 inches Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
Between 0.315 inches and 0.335 inches Undercut Diameter: Between 0.141 inches and 0.146 inches Undercut Width: Between 0.025 inches and 0.055 inches Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
Undercut Diameter: Between 0.141 inches and 0.146 inches Undercut Width: Between 0.025 inches and 0.055 inches Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
Between 0.141 inches and 0.146 inches Undercut Width: Between 0.025 inches and 0.055 inches Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
Undercut Width:  Between 0.025 inches and 0.055 inches  Second Undercut Width:  Between 0.090 inches and 0.130 inches  Second Undercut Diameter:  Between 0.162 inches and 0.167 inches  First End Taper Length:  0.020 inches  Second End Relationship With First End:  Identical  Hardness Rating:
Between 0.025 inches and 0.055 inches  Second Undercut Width:  Between 0.090 inches and 0.130 inches  Second Undercut Diameter:  Between 0.162 inches and 0.167 inches  First End Taper Length:  0.020 inches  Second End Relationship With First End:  Identical  Hardness Rating:
Second Undercut Width: Between 0.090 inches and 0.130 inches Second Undercut Diameter: Between 0.162 inches and 0.167 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
Between 0.090 inches and 0.130 inches  Second Undercut Diameter:  Between 0.162 inches and 0.167 inches  First End Taper Length:  0.020 inches  Second End Relationship With First End:  Identical  Hardness Rating:
Second Undercut Diameter:  Between 0.162 inches and 0.167 inches  First End Taper Length: 0.020 inches  Second End Relationship With First End: Identical  Hardness Rating:
Between 0.162 inches and 0.167 inches  First End Taper Length: 0.020 inches  Second End Relationship With First End: Identical  Hardness Rating:
First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating:
0.020 inches  Second End Relationship With First End: Identical Hardness Rating:
Second End Relationship With First End: Identical Hardness Rating:
Identical Hardness Rating:
Hardness Rating:
•
32.0 rockwell c and 36.0 rockwell c
Second Shank Diameter:
Between 0.1724 inches and 0.1729 inches
First End Location:
Both ends
First End Taper Angle:
45.0 degrees
Surface Finish:
63.0 microinches large shank
Second Shank Length:
Between 0.090 inches and 0.130 inches
Material:
Stainless steel
Material Specification:
Ams 5655 assn standard single material response
Style Designator:
Undercut
Shelf Life:
N/a

## NSN 5315-00-519-9526

Headless Shoulder Pin - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0