## NSN 5315-00-520-2829

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-520-2829

| First End Style:                        |
|---|
| Chamfered                               |
| Shank Length:                           |
| Between 0.180 inches and 0.195 inches   |
| Shoulder Diameter:                      |
| Between 0.1567 inches and 0.1572 inches |
| Shank Diameter:                         |
| Between 0.092 inches and 0.096 inches   |
| Overall Length:                         |
| Between 0.490 inches and 0.510 inches   |
| First End Taper Length:                 |
| 0.016 inches                            |
| Second End Relationship With First End: |
| Identical                               |
| Hardness Rating:                        |
| 50.0 rockwell c and 55.0 rockwell c     |
| Second Shank Diameter:                  |
| Between 0.092 inches and 0.096 inches   |
| First End Location:                     |
| Both ends                               |
| First End Taper Angle:                  |
| Between 40.0 degrees and 50.0 degrees   |
| Second Shank Length:                    |
| Between 0.180 inches and 0.195 inches   |
| Material:                               |
| Steel comp 4140 or steel comp 8740      |
| Surface Treatment:                      |
| Nickel                                  |
| Style Designator:                       |
| Shoulder                                |
| Shelf Life:                             |
| N/a                                     |
| Unit Of Measure:                        |
|   |
| Demilitarization:                       |
| No                                      |
| Fiig:                                   |
| A212a0                                  |
|   |
|   |