

View Online at <https://aerobasegroup.com/nsn/5315-00-523-0922>

**Head Diameter:**

Between 0.410 inches and 0.470 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Detent Quantity:**

2

**Grip Length:**

Between 1.100 inches and 1.120 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.125 inches

**Pin Center To Handle End Distance:**

Between 0.645 inches and 0.775 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.290 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

Cam lever

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6736 spec.