NSN 5315-00-531-0581

Between 0.385 inches and 0.395 inches

Between 0.4390 inches and 0.4395 inches

Between 0.2485 inches and 0.2490 inches

First End Style: Chamfered Shank Length:

Shoulder Diameter:

Shank Diameter:

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-531-0581

Overall Length:
3.031 inches
Hole Arrangement Style:
Both end drilled
First Hole Diameter:
0.076 inches
Second Hole Diameter:
0.076 inches
Distance From Centerline Of Hole To End Of Pin:
Between 0.790 inches and 0.810 inches
Center To Center Distance Between Holes:
1.430 inches
First End Taper Length:
0.031 inches
Second End Relationship With First End:
Identical
Hardness Rating:
34.0 rockwell c and 38.0 rockwell c
Second Shank Diameter:
Between 0.385 inches and 0.395 inches
First End Location:
Both ends
First End Taper Angle:
45.0 degrees
Criticality Code Justification:
Aavh and aaze
Second Shank Length:
Between 0.385 inches and 0.395 inches
Special Features:
Both shank ends chamfered 0.031 in. By 45 degrees on edges not cited in abql and abqm
Material:
Steel comp 1095
Style Designator:
Shoulder

NSN 5315-00-531-0581

Headless Shoulder Pin - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0