

View Online at <https://aerobasegroup.com/nsn/5315-00-535-6992>

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.667 inches

Shank Length:

0.750 inches

Shoulder Diameter:

Between 0.427 inches and 0.447 inches

Shank Diameter:

Between 0.367 inches and 0.374 inches

Overall Length:

Between 1.427 inches and 1.447 inches

Undercut Diameter:

Between 0.306 inches and 0.316 inches

Undercut Width:

0.083 inches

First End Taper Length:

Between 0.115 inches and 0.135 inches

Second End Taper Length:

0.031 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.375 inches

Second Shank Diameter:

Between 0.366 inches and 0.371 inches

First End Location:

Shank end

First End Taper Angle:

30.0 degrees

Second End Taper Angle:

45.0 degrees

Second Shank Length:

0.667 inches

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, class c federal specification single treatment response

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.