

View Online at <https://aerobasegroup.com/nsn/5315-00-535-6992>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.667 inches

**Shank Length:**

0.750 inches

**Shoulder Diameter:**

Between 0.427 inches and 0.447 inches

**Shank Diameter:**

Between 0.367 inches and 0.374 inches

**Overall Length:**

Between 1.427 inches and 1.447 inches

**Undercut Diameter:**

Between 0.306 inches and 0.316 inches

**Undercut Width:**

0.083 inches

**First End Taper Length:**

Between 0.115 inches and 0.135 inches

**Second End Taper Length:**

0.031 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**Second Shank Diameter:**

Between 0.366 inches and 0.371 inches

**First End Location:**

Shank end

**First End Taper Angle:**

30.0 degrees

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

0.667 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, class c federal specification single treatment response

**Style Designator:**

Undercut

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.