## NSN 5315-00-536-6854

Headless Grooved Pin - Page 1 of 2

First End Style:



View Online at https://aerobasegroup.com/nsn/5315-00-536-6854

Chamfered and countersunk
Second End Style:
Chamfered and countersunk
Overall Length:
3.380 inches
Diameter:
Between 0.7495 inches and 0.7500 inches
Effective Length:
2.415 inches
Undercut Diameter:
0.400 inches
Undercut Width:
0.125 inches
Undercut Radius:
0.125 inches
First End Taper Length:
0.125 inches
Second End Taper Length:
0.715 inches
Second End Relationship With First End:
Not identical
Shear Strength:
220000 single pounds per square inch
Second End Countersink Angle:
100.0 degrees
First End Location:
Both ends
First End Taper Angle:
30.0 degrees
First End Countersink Angle:
60.0 degrees
Surface Finish:
8.0 microinches outside diameter
First End Countersink Diameter:
0.250 inches
Second End Taper Angle:
7.5 degrees
Second End Countersink Diameter:
0.363 inches
Material:

Steel comp xm-13

## NSN 5315-00-536-6854

Headless Grooved Pin - Page 2 of 2



		tor:

Groove

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0