NSN 5315-00-539-4384

Threaded Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-539-4384

| First End Style |
|--|
| First End Style: |
| Chamfered |
| Thread Class: |
| 2a There d Directions |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.330 inches and 0.360 inches |
| Pinlength: |
| Between 4.150 inches and 4.220 inches Pindiameter: |
| Between 0.2460 inches and 0.2480 inches |
| |
| First End Taper Length: Between 0.020 inches and 0.022 inches |
| |
| Thready Qty Per Inch (tpi): 32 |
| Second End Relationship With First End: |
| Identical |
| Thread Size: |
| 0.164 inches |
| First End Location: |
| Unthreaded end |
| First End Taper Angle: |
| 45.0 degrees |
| Pin Grip Length: |
| Between 0.330 inches and 0.360 inches |
| Surface Finish: |
| 63.0 microinches outside diameter |
| Special Features: |
| Large end knurled 0.320 in.Min 0.440 in.Max from end |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-225/8 federal specification single material response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5315-00-539-4384 Threaded Straight Pin - Page 2 of 2

Fiig: A212a0

