## NSN 5315-00-539-5467

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-539-5467 **Head Diameter:** Between 0.640 inches and 0.755 inches **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 2.100 inches and 2.120 inches **Actuation Type:** Pull and push Hardness Rating: 36.0 rockwell c shank and 40.0 rockwell c shank **Shear Strength:** 32800 double pounds per square inch **Shoulder To Head End Distance:** 1.270 inches Pin Center To Handle End Distance: Between 1.530 inches and 1.655 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.540 inches and 0.590 inches Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A212a0

## NSN 5315-00-539-5467

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.