# NSN 5315-00-544-3180

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-544-3180

## Head Diameter:

Between 0.640 inches and 0.755 inches

## Shank Diameter:

Between 0.4970 inches and 0.4985 inches

## **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

## **Detent Quantity:**

2

## **Actuation Method:**

Push button

Grip Length:

Between 3.300 inches and 3.320 inches

## Actuation Type:

Pull and push

### Hardness Rating:

40.0 rockwell c spindle

## Shoulder To Head End Distance:

1.070 inches

## Pin Attachment Type:

Hook or ring

# Detent To Tapered End Distance:

0.590 inches

## Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

## Surface Treatment:

Passivate spindle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

Ring handle

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A212a0