# NSN 5315-00-546-3463

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-546-3463

## Head Diameter:

Between 0.640 inches and 0.755 inches

## Shank Diameter:

Between 0.4970 inches and 0.4985 inches

## **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

## **Detent Quantity:**

2

#### **Actuation Method:**

Push button

Grip Length:

Between 2.300 inches and 2.320 inches

#### **Actuation Type:**

Pull and push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

## Shoulder To Head End Distance:

1.070 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

Between 0.540 inches and 0.590 inches

## Material:

Steel comp 4130 spindle

## **Material Specification:**

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

## Surface Treatment:

Cadmium spindle and chromate spindle

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

## Style Designator:

Ring handle

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A212a0

## Mil-std (military Standard):

Mil-t-6736 spec.