NSN 5315-00-564-6625

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-564-6625 First End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand **Thread Length:** 0.329 inches **Shank Length:** 0.312 inches **Shoulder Diameter:** Between 0.186 inches and 0.187 inches **Shank Diameter:** Between 0.146 inches and 0.149 inches **Overall Length:** 1.547 inches **Undercut Diameter:** 0.125 inches **Undercut Width:** 0.031 inches **Second Undercut Width:** 0.031 inches First End Taper Length: 0.031 inches Second End Relationship With First End: Identical **Thread Size:** 0.164 inches **Second Shank Diameter:** 0.164 inches First End Location: Both ends First End Taper Angle: 45.0 degrees **Second Shank Length:** 0.329 inches **Special Features:** Unthreaded end has straight knurl 0.031 in. From end to groove Material: Steel comp 303

Passivate

Surface Treatment:

NSN 5315-00-564-6625

Headless Shoulder Pin - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Undercut

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.