## NSN 5315-00-567-5799

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-567-5799

First End Style
First End Style:
Square
Thread Class:
2a Thread Directions
Thread Direction:
Right-hand
Thread Length:
0.312 inches
Shank Length:
1.262 inches
Shoulder Width Across Flats:
0.312 inches
Shank Diameter:
Between 0.1840 inches and 0.1855 inches
Overall Length:
1.844 inches
Undercut Diameter:
0.156 inches
Undercut Width:
0.047 inches
Features Provided:
Casehardened
Second End Relationship With First End:
Identical
Thread Size:
0.164 inches
Second Shank Diameter:
0.164 inches
First End Location:
Both ends
Second Shank Length:
0.375 inches
Special Features:
$0.047 \mbox{ in. W},  0.147 \mbox{ in. Min},  0.149 \mbox{ in. Maximum diameter undercut on shank diameter end}$
Material:
Steel comp b1112
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232 ty mcl 2 military specification single treatment response
Style Designator:
Undercut

## NSN 5315-00-567-5799

Headless Shoulder Pin - Page 2 of 2



**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A212a0

## Mil-std (military Standard):

Mil-p-16232 spec.