## NSN 5315-00-582-1522

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-582-1522

First End Style:
Chamfered
Overall Length:
Between 0.812 inches and 0.832 inches
Diameter:
Between 0.2490 inches and 0.2495 inches
Effective Length:
Between 0.510 inches and 0.520 inches
Undercut Diameter:
Between 0.2285 inches and 0.2315 inches
Undercut Width:
Between 0.028 inches and 0.031 inches
First End Taper Length:
Between 0.021 inches and 0.041 inches
Second End Relationship With First End:
Identical
Hardness Rating:
265.0 brinell hultgren and 290.0 brinell hultgren
First End Location:
Both ends
First End Taper Angle:
Between 40.0 degrees and 50.0 degrees
Surface Finish:
32.0 microinches shank end
Material:
Steel comp w110
Material Specification:
Mil-t-18291, class w1-ndr military specification single material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-p-16232, type 1 military specification single treatment response
Style Designator:
Groove
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

## NSN 5315-00-582-1522

Headless Grooved Pin - Page 2 of 2

Mil-std (military Standard):

Mil-t-18291 spec.

