

View Online at <https://aerobasegroup.com/nsn/5315-00-584-1639>

**Head Style:**

Flat fillister

**Diameter:**

Between 0.123 inches and 0.125 inches

**Under Head Length:**

0.531 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.046 inches and 0.048 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.047 inches and 0.078 inches

**Pin Head Diameter:**

Between 0.170 inches and 0.172 inches

**Surface Finish:**

125.0 microinches

**Special Features:**

Shank has undercut 0.1155 to 0.1185 in. Diameter by 0.010 to 0.014 in. W

**Height:**

Between 0.240 inches and 0.250 inches

**Material:**

Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 262 or copper alloy 270 or copper alloy 272 or copper alloy 274 or copper alloy 280 or copper alloy 330 or copper alloy 331 or copper alloy 332 or copper alloy 335 or copper alloy 340 or copper alloy 344 or copper alloy 345 or copper alloy 347 or copper alloy 348 or copper alloy 350 or copper alloy 356 or copper alloy 370 or copper alloy 462 or copper alloy 464 or copper alloy 465 or copper alloy 466 or copper alloy 467 or copper alloy 482

**Material Specification:**

Qq-b-626 federal specification all material responses

**Surface Treatment:**

Tin

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0