

View Online at <https://aerobasegroup.com/nsn/5315-00-584-1696>

First End Style:

Slotted

Second End Style:

Square

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.312 inches

Shank Length:

0.312 inches

Shoulder Diameter:

0.156 inches

Shank Diameter:

0.138 inches

Overall Length:

1.000 inches

Internal Drive Style:

Slot

First End Slot Width:

0.040 inches

First End Slot Depth:

0.040 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.138 inches

First End Location:

Threaded end

Special Features:

0.040 in. By 0.040 in. Slot across shoulder end dia

Material:

Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 356 or copper alloy 360 or copper alloy 377 or copper alloy 262 or copper alloy 270 or copper alloy 272 or copper alloy 274 or copper alloy 280 or copper alloy 330 or copper alloy 331 or copper alloy 332 or copper alloy 335 or copper alloy 340 or copper alloy 344 or copper alloy 345 or copper alloy 347 or copper alloy 348 or copper alloy 350 or copper alloy 356 or copper alloy 370 or copper alloy 356 or copper alloy 370 or copper alloy 462 or copper alloy 464 or copper alloy 465 or copper alloy 466 or copper alloy 467 or copper alloy 482

Surface Treatment:

Nickel

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0